

## Magnetic Liquid Level Gages

### Rugged, Versatile Options for a Wide Range of Applications

MULTIVIEW™ Magnetic Liquid Level Gages utilize a communicating chamber constructed of 2-1/2" pipe which is connected to the process tank with either side or end connections. A float with a self-enclosed magnet is custom sized and weighted to float at the surface of the process liquid to be monitored. The float is then installed in the communicating chamber.

The industry-unique concentric magnet in MULTIVIEW™ gages provides a more consistent magnetic field than conventional magnet designs.



### Construction Materials Available

Penberthy offers a wide range of materials, including:

- 304/304L STS
- 316/316L STS
- Alloy-20
- Monel
- Titanium
- Hastelloy-C
- PVC
- CPVC
- PVDF
- Tefzel® Lined

Halar® Lined

### Typical Process Applications

- |  |  |   |
|--|--|---|
| <ul style="list-style-type: none"> <li>• Sodium Hypochlorite</li> <li>• Boiler Feedwater Tank</li> <li>• Hydrochloric Acid</li> <li>• Stop Oil</li> <li>• LPG</li> <li>• Interface</li> <li>• Dowtherm®</li> <li>• Sulfuric Acid</li> <li>• Hydrogen Sulfide</li> <li>• Oil/Water Separator</li> <li>• Sodium Hydroxide</li> <li>• Liquid Nitrogen</li> <li>• Flare Drums</li> </ul> | <ul style="list-style-type: none"> <li>• Ammonia</li> <li>• Butane</li> <li>• Seal Oil Pots</li> <li>• Black Liquor</li> <li>• Drip Pot</li> <li>• Boiler Steam Drums</li> <li>• Glycol</li> <li>• Propane</li> <li>• Hydraulic Oil</li> <li>• Feedwater Heaters</li> <li>• Extreme Flashing</li> <li>• Hydrazine</li> <li>• Caustic Chemicals</li> <li>• Fuel Oil</li> <li>• Hydrofluoric Acid</li> </ul> | <ul style="list-style-type: none"> <li>• Jet Fuel</li> <li>• Molten Sulfur</li> <li>• Sour Oil</li> <li>• Diesel Fuel</li> <li>• Deionized Water</li> <li>• Sumps</li> <li>• Freon</li> <li>• Liquid Ethylene</li> <li>• Water</li> <li>• Underground Storage</li> <li>• Benzene</li> <li>• Asphalt Settler</li> <li>• Acetic Acid</li> <li>• Liquids &amp; Slurries</li> </ul> |
|--|--|---|

